

SEA CONTAINER SPECIFICATIONS

DRY CARGO CONTAINERS

Dimensions



Type	Container Weight			Interior Measurement				Door Open	
	Gross (kg)	Tare (kg)	Net (kg)	Length (m)	Width (m)	Height (m)	Capacity (m ³)	Width (m)	Height (m)
20' DC	24,000	2,370	21,630	5.898	2.352	2.394	33.20	2.343	2.280
40' DC	30,480	4,000	26,480	12.031	2.352	2.394	67.74	2.343	2.280

CHARACTERISTICS

Manufactured from either Aluminium or steel, they are suitable for most types of cargo / general cargo. Aluminium containers have a slightly larger payload than steel, and steel containers have a slightly larger internal cube.

HIGH CUBE CONTAINERS

Dimensions



Type	Container Weight			Interior Measurement				Door Open	
	Gross (kg)	Tare (kg)	Net (kg)	Length (m)	Width (m)	Height (m)	Capacity (m ³)	Width (m)	Height (m)
40' HC	30,480	3,980	26,500	12.031	2.352	2.698	76.30	2.340	2.585
45' HC	30,480	4,800	25,680	13.544	2.352	2.698	86.00	2.340	2.585

CHARACTERISTICS

With high cube containers, you gain an extra foot in height compared with general-purpose containers. Ideal for light, voluminous cargo or bulky cargo. These extra volume containers come in steel and aluminium.

REFRIGERATED CONTAINERS

Dimensions



Type	Container Weight			Interior Measurement				Door Open	
	Gross (kg)	Tare (kg)	Net (kg)	Length (m)	Width (m)	Height (m)	Capacity (m ³)	Width (m)	Height (m)
20' RF	24,000	3,050	20,950	5.449	2.290	2.244	26.70	2.276	2.261
40' RF	30,480	4,520	25,960	11.690	2.250	2.247	57.10	2.280	2.205

CHARACTERISTICS

Recommended for delicate cargo. Bottom-air delivery system ensures refrigerated cargo reaches its destination in optimum condition.

OPEN TOP CONTAINERS

Dimensions



Type	Container Weight			Interior Measurement				Door Open	
	Gross (kg)	Tare (kg)	Net (kg)	Length (m)	Width (m)	Height (m)	Capacity (m ³)	Width (m)	Height (m)
20' OT	24,000	2,580	21,420	5.629	2.212	2.311	32.00	2.330	2.263
40' OT	30,480	4,290	26,190	11.763	2.212	2.311	65.40	2.330	2.263

CHARACTERISTICS

Allowing cargo to be loaded from the top, open top containers are particularly suitable for bulky cargo such as machinery. They are fitted with a PVC tarpaulin cover and attachable bows with cable sealing devices. The container doors can be removed to make the stuffing of cargo more convenient. Manufactured from steel.

FLAT RACK CONTAINERS

Dimensions



Type	Container Weight			Interior Measurement			
	Gross (kg)	Tare (kg)	Net (kg)	Length (m)	Width (m)	Height (m)	Capacity (m ³)
20' FR	30,480	2,900	27,580	5.624	2.236	2.234	27.90
40' FR	34,000	5,870	28,130	11.786	2.236	1.968	51.90

CHARACTERISTICS

Flatracks are especially suited to heavy loads or cargo that needs loading from the top or sides, such as pipes and machinery. There are collapsible and non-collapsible containers with or without walls. Manufactured from steel.

20" STANDARD

INSIDE LENGTH	5.895 m
INSIDE WIDTH	2.350 m
INSIDE HEIGHT	2.392 m
DOOR WIDTH	2.340 m
DOOR HEIGHT	2.292 m
CAPACITY	33 m3
TARE WEIGHT	2230 Kgs
MAX CARGO WEIGHT	28230 Kgs

40" STANDARD

INSIDE LENGTH	12.029 m
INSIDE WIDTH	2.350 m
INSIDE HEIGHT	2.392 m
DOOR WIDTH	2.340 m
DOOR HEIGHT	2.292 m
CAPACITY	67 m3
TARE WEIGHT	3780 Kgs
MAX CARGO WEIGHT	26700 Kgs

40" HIGH-CUBE

INSIDE LENGTH	12.024 m
INSIDE WIDTH	2.350 m
INSIDE HEIGHT	2.697 m
DOOR WIDTH	2.340 m
DOOR HEIGHT	2.597 m
CAPACITY	76 m3
TARE WEIGHT	4020 Kgs
MAX CARGO WEIGHT	26460 Kgs

20" OPEN TOP

INSIDE LENGTH	5.888 m
INSIDE WIDTH	2.345 m
INSIDE HEIGHT	2.315 m
DOOR WIDTH	2.286 m
DOOR HEIGHT	2.184 m
CAPACITY	32 m3
TARE WEIGHT	2250 Kgs
MAX CARGO WEIGHT	30480 Kgs

40" OPEN TOP

INSIDE LENGTH	12.029 m
INSIDE WIDTH	2.342 m
INSIDE HEIGHT	2.326 m
DOOR WIDTH	2.341 m
DOOR HEIGHT	2.274 m
CAPACITY	65 m3
TARE WEIGHT	3810 Kgs
MAX CARGO WEIGHT	26670 Kgs

20" FLATRACK

INSIDE LENGTH	5.698 m
INSIDE WIDTH	2.230 m
INSIDE HEIGHT	2.255 m
DOOR WIDTH	0.000 m
DOOR HEIGHT	0.000 m
CAPACITY	0 m3
TARE WEIGHT	2500 Kgs
MAX CARGO WEIGHT	21500 Kgs

40" FLATRACK


INSIDE LENGTH	11.832 m
INSIDE WIDTH	2.228 m
INSIDE HEIGHT	1.981 m
DOOR WIDTH	0.000 m
DOOR HEIGHT	0.000 m
CAPACITY	0 m3
TARE WEIGHT	4200 Kgs
MAX CARGO WEIGHT	40800 Kgs

20" REFRIGERATED

INSIDE LENGTH	5.724 m
INSIDE WIDTH	2.286 m
INSIDE HEIGHT	2.014 m
DOOR WIDTH	2.286 m
DOOR HEIGHT	2.067 m
CAPACITY	26 m3
TARE WEIGHT	2550 Kgs
MAX CARGO WEIGHT	21450 Kgs

40" REFRIGERATED

INSIDE LENGTH	11.840 m
INSIDE WIDTH	2.286 m
INSIDE HEIGHT	2.120 m
DOOR WIDTH	2.286 m
DOOR HEIGHT	2.195 m
CAPACITY	60 m3
TARE WEIGHT	3850 Kgs
MAX CARGO WEIGHT	26630 Kgs

20" TANK

INSIDE LENGTH	6.058 m
INSIDE WIDTH	2.438 m
INSIDE HEIGHT	2.438 m
DOOR WIDTH	0.000 m
DOOR HEIGHT	0.000 m
CAPACITY	0 m3
TARE WEIGHT	4190 Kgs
MAX CARGO WEIGHT	26290 Kgs